

120 Valley Court Oak Ridge, TN 37830 Ph: 865-482-5717 FAX: 865-482-1281 zypcoatings.com

Boron Nitride Lubricoat[®] Boron Nitride Lubricoat-Blue[®]

Our Best, All-purpose, Coating Concentrate

BN Lubricoat is our proven "workhorse" release agent for high-temperature use. BN Lubricoat® is ideal for providing true non-wetting for all liquid metal transfer system components. Also, BN Lubricoat is non-reactive and non-stick with glass, slags, fluxes. As a lubricant/non-stick agent, BN Lubricoat is ideal for hot-pressing and glass forming.

Key Attributes

- Totally Non-Wetted by Molten Aluminum, Magnesium, Zinc and Their Drosses
- Protects Ceramics, Metals and Graphite
- Maintenance is Reduced and Operator Satisfaction Maximized
- Applied Like House paint
- Safe, Water-Based, No VOC's

Ideal Use

- Launders & Runners
- Auto-Pour Ladles
- Troughs & Tubes
- Funnels & Spouts
- Filter Bowls, Boxes
- Caster Tips
- Dross Press Heads
- Braze Stop-Off
- Weld Spatter Release

Use Notes

- 1. Resuspend if needed. Can dilute with water.
- 2. Clean surfaces to be painted of any oils dirt, scale, etc.
- 3. Apply one thin layer by brush, dip or spray like ordinary house paint
- 4. Allow to dry thoroughly before use.

Safety Information

- Consult SDS before use.
- Avoid breathing of spray/vapors.
- For Industrial Use only.



Specifications

Use Atmosphere Fired Composition Liquid Carrier Binder Phase Al ₂ O ₃ Active Ingredient Level Brookfield Viscosity (cps) Specific Gravity Color White, except when specified blue Shelf Life (months Coverage (ft²/gal) Session all
Fired Composition >85% BN Liquid Carrier Water Binder Phase Al ₂ O ₃ Active Ingredient Level Fully Loaded Brookfield Viscosity (cps) 900-1150 @3/60 Specific Gravity 1.2 Color White, except when specified blue Shelf Life (months >12 Coverage (ft²/gal) 100 to 400
Binder Phase Al ₂ O ₃ Active Ingredient Level Fully Loaded Brookfield Viscosity (cps) 900-1150 @3/60 Specific Gravity 1.2 Color White, except when specified blue Shelf Life (months >12 Coverage (ft²/gal) 100 to 400
Active Ingredient Level Fully Loaded Brookfield Viscosity (cps) 900-1150 @3/60 Specific Gravity 1.2 Color White, except when specified blue Shelf Life (months >12 Coverage (ft²/gal) 100 to 400
Brookfield Viscosity (cps) 900-1150 @3/60 Specific Gravity 1.2 Color White, except when specified blue Shelf Life (months >12 Coverage (ft²/gal) 100 to 400
Specific Gravity 1.2 Color White, except when specified blue Shelf Life (months >12 Coverage (ft²/gal) 100 to 400
Color White, except when specified blue Shelf Life (months >12 Coverage (ft²/gal) 100 to 400
Shelf Life (months >12 Coverage (ft²/gal) 100 to 400
Coverage (ft²/gal) 100 to 400
Coating all
Coating pH 2-4
H F R Ratings 1-0-0
Substrate Use All

Sizes and colors

Boron Nitride Lubricoat is a white colored paint. Boron Nitride Lubricoat-Blue is a blue colored paint that may offer better visibility. We also offer a white paste for uses where a thicker version of our Boron Nitride Lubricoat is needed: BN Lubricoat Paste.

Standard Size: wide-mouth 1 gallon pail. Also available in 5 gallon pail upon request. Blue version also available in a 6 liter (1.59 gallon) keg with easy opening screw lid.

CAUTION: DO NOT CONTACT WET COATINGS WITH MOLTEN METAL.

ZYP Coatings, Inc. (ZYP) makes no warranties, express or implied, including the warranty of merchantability or fitness for a particular service. Product is for industrial/commercial use only. Users should determine suitability for their use. In no event will ZYP be liable for any direct, indirect, incidental, special or consequential damages or losses including, but not limited to loss of profits, in any way related to this product regardless of the legal theory asserted.