

120 Valley Court Oak Ridge, TN 37830 Ph: 865-482-5717 FAX: 865-482-1281 zypcoatings.com

# Boron Nitride Releasecoat<sup>®</sup> Boron Nitride Releasecoat-Blue<sup>®</sup>

## For Permanent Mold or Low Pressure Casting, Get Excellent Mold Release

BN Releasecoat<sup>®</sup> is a relatively-soft, washcoat-type of coating with a lower BN content which still provides excellent nonwetting and release with aluminum, magnesium, zinc and other nonferrous metals and alloys.

### **Key Attributes**

- Perfect for top-coating over thermal insulating coatings.
- Provides "cosmetic"/mirror-like surface finish with excellent mold release
- Ideal for low-draft, high-drag regions for wheel casting
- Easily applied by air spraying on to hot or cold molds
- Readily touch up molds while hot
- Safe, water-based

#### **Ideal Use**

- Permanent Molds
- Low Pressure or Gravity Die casting

#### **Use Notes**

- 1. Resuspend if needed. Can dilute with water.
- 2. Clean surfaces to be painted of any oils dirt, scale, etc.
- 3. Apply 1-3 layers by brush or spray like ordinary house paint, drying after each layer
- 4. Allow to dry thoroughly at room temperature before use.

## **Safety Information**

- Consult SDS before use.
- Avoid breathing of spray/vapors.
- For Industrial Use only.



## Specifications

| Active Ingredient BN<br>Max Use Temperature Air 1832 F / 1000 C<br>Vac 2552 F / 1400 C<br>Inert 3272 F / 1800 C |
|---|
| Use Atmosphere All  |
| Fired Composition >85% BN   |
| Liquid Carrier Water  |
| Binder Phase Magnesium Silicate   |
| Active Ingredient Level Low Loading   |
| Brookfield Viscosity (cps) 300-500 @2/60  |
| Specific Gravity 1  |
| Color White, except when specified blue   |
| Shelf Life (months) >12   |
| Coverage (ft <sup>2</sup> /gal) 100 to 400  |
| Coating pH 7-8  |
| H F R Ratings 1-0-0   |
| Substrate Use All   |

#### Sizes and colors

BN Releasecoat is a white colored paint. BN Releasecoat-Blue is a blue colored paint that may offer better visibility.

Standard Size: wide-mouth 1 gallon pail.

#### CAUTION: DO NOT CONTACT WET COATINGS WITH MOLTEN METAL.

ZYP Coatings, Inc. (ZYP) makes no warranties, express or implied, including the warranty of merchantability or fitness for a particular service. Product is for industrial/commercial use only. Users should determine suitability for their use. In no event will ZYP be liable for any direct, indirect, incidental, special or consequential damages or losses including, but not limited to loss of profits, in any way related to this product regardless of the legal theory asserted.