



120 Valley Court
Oak Ridge, TN 37830
Ph: 865-482-5717
FAX: 865-482-1281
zypcoatings.com

Boron Nitride Lubriccoat®-ZS Boron Nitride Lubriccoat-Blue®-ZS

Highly Dilutable Paint

BN Lubriccoat®-ZS is the same as our regular BN Lubriccoat® except for using a hydrochloric-acid "peptizer" instead of nitric-acid. The "ZS" version is thus somewhat better in adherence and also more dilutable with water than our regular BN Lubriccoat. The "ZS" works well as long as the surface/substrate is OK with this type of acidic (like lemon juice) carrier.

Key Attributes

- Totally Non-Wetted by Molten Aluminum, Magnesium, Zinc and Their Drosses
- Protects Ceramics, Metals and Graphite
- Maintenance is Reduced and Operator Satisfaction Maximized
- Dilutable to Most Any Level
- Applied Like House paint
- Safe, Water-Based, No VOC's

Ideal Use

- Launderers & Runners
- Auto-Pour Ladles
- Troughs & Tubes
- Funnels & Spouts
- Filter Bowls, Boxes
- Caster Tips
- Dross Press Heads

Use Notes

1. Resuspend if needed. OK to dilute with water with 2 parts water to 1 part coating as normal.
2. Clean surfaces to be painted of any oils dirt, scale, etc.
3. Apply one thin layer by brush, dip, or spray like ordinary house paint
4. Allow to dry thoroughly before use.

Safety Information

- Consult SDS before use.
- Avoid breathing of spray/vapors.
- For Industrial Use only.



Specifications

Active Ingredient	BN
Max Use Temperature	Air 1800 F / 1000 C Vac 2552 F / 1400C Inert 3272 F / 1800C
Use Atmosphere	All
Fired Composition	>85% BN
Liquid Carrier	Water
Binder Phase	Al ₂ O ₃
Active Ingredient Level	Fully Loaded
Brookfield Viscosity (cps)	1500-2500 @4/60
Specific Gravity	1.2
Color	White, except when specified blue
Shelf Life (months)	>12
Coverage (ft ² /gal)	100 to 400
Coating pH	2-4
H F R Ratings	1-0-0
Substrate Use	All

Sizes and colors

Boron Nitride Lubriccoat-ZS is a white colored paint. Boron Nitride Lubriccoat-Blue-ZS is a blue colored paint that may offer better visibility.

Standard Size: wide-mouth 1 gallon pail.
Also available in 5 gallon pail upon request.

CAUTION: DO NOT CONTACT WET COATINGS WITH MOLTEN METAL.

ZYP Coatings, Inc. (ZYP) makes no warranties, express or implied, including the warranty of merchantability or fitness for a particular service. Product is for industrial/commercial use only. Users should determine suitability for their use. In no event will ZYP be liable for any direct, indirect, incidental, special or consequential damages or losses including, but not limited to loss of profits, in any way related to this product regardless of the legal theory asserted.